## **AKTL 629/S**


12NC: 859991590770

GTIN (EAN) code: 8003437605321



SENSING THE DIFFERENCE





Product group Built-in Type of control Mechanical Type of control Mechanical Type of control Settings Knob Number of gas burners 4 Number of electric cooking zones 0 Number of electric plates 0 Number of radiant plates 0 Number of induction plates 0 Number of electric warming zones 0 Number of ocntrol panel Front Basic surface material Glass Main colour of product Silver Dawn Electrical connection rating (W) 7800 Gas connection rating (W) 7800 Gas type 620 Current (A) 0,6 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 85 Plug type No Gas connection M/A Width of the product 590 Height of the product 560 Minimum niche height 41 Minimum niche width 560 Niche depth 490 Net weight (kg) 12.3 Automatic programmes	PÕHIOMADUSED	
Type of control Type of control settings Number of gas burners Number of electric cooking zones Number of electric plates Number of radiant plates Number of halogen plates Number of induction plates Number of electric warming zones Location of control panel Basic surface material Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Gas connection Silver Dawn Front Silver Dawn Silver Dawn Front Front Silver Dawn Front Silver Dawn Front Silver Dawn Front Front Silver Dawn Front Silver Dawn Front Front Silver Dawn Front	Product group	Hob
Type of control settings  Number of gas burners  Number of electric cooking zones  Number of electric plates  Number of radiant plates  Number of halogen plates  Number of induction plates  Number of electric warming zones  Location of control panel  Basic surface material  Basic surface material  Glass  Main colour of product  Electrical connection rating (W)  Gas connection rating (W)  Gas type  Current (A)  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  Gas connection  N/A  Width of the product  Minimum niche height  Minimum niche width  Niche depth  Net weight (kg)  Net weight (kg)  No  O  O  Number of electric cooking zones  O  O  O  O  O  O  O  O  Number of adiant plates  O  O  O  O  O  O  O  Number of adiant plates  O  O  O  O  Number of electric alles  O  O  O  O  O  O  O  O  O  Silver Dawn  O  O  O  O  O  O  O  O  O  O  O  O  O	Construction type	Built-in
Number of gas burners4Number of electric cooking zones0Number of electric plates0Number of radiant plates0Number of induction plates0Number of electric warming zones0Location of control panelFrontBasic surface materialGlassMain colour of productSilver DawnElectrical connection rating (W)7800Gas typeG20Current (A)0,6Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)85Plug typeNoGas connectionN/AWidth of the product590Height of the product49Depth of the product510Minimum niche height41Minimum niche width560Niche depth490Net weight (kg)12.3	Type of control	Mechanical
Number of electric cooking zones0Number of electric plates0Number of radiant plates0Number of induction plates0Number of electric warming zones0Location of control panelFrontBasic surface materialGlassMain colour of productSilver DawnElectrical connection rating (W)7800Gas typeG20Current (A)0,6Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)85Plug typeNoGas connectionN/AWidth of the product590Height of the product49Depth of the product510Minimum niche height41Minimum niche width560Niche depth490Net weight (kg)12.3	Type of control settings	Knob
Number of electric plates0Number of radiant plates0Number of halogen plates0Number of induction plates0Number of electric warming zones0Location of control panelFrontBasic surface materialGlassMain colour of productSilver DawnElectrical connection rating (W)0Gas connection rating (W)7800Gas typeG20Current (A)0,6Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)85Plug typeNoGas connectionN/AWidth of the product590Height of the product49Depth of the product510Minimum niche height41Minimum niche width560Niche depth490Net weight (kg)12.3	Number of gas burners	4
Number of radiant plates       0         Number of induction plates       0         Number of induction plates       0         Number of electric warming zones       0         Location of control panel       Front         Basic surface material       Glass         Main colour of product       Silver Dawn         Electrical connection rating (W)       0         Gas connection rating (W)       7800         Gas type       G20         Current (A)       0,6         Voltage (V)       220-240         Frequency (Hz)       50/60         Length of Electrical Supply Cord (cm)       85         Plug type       No         Gas connection       N/A         Width of the product       590         Height of the product       49         Depth of the product       510         Minimum niche height       41         Minimum niche width       560         Niche depth       490         Net weight (kg)       12.3	Number of electric cooking zones	0
Number of halogen plates       0         Number of induction plates       0         Number of electric warming zones       0         Location of control panel       Front         Basic surface material       Glass         Main colour of product       Silver Dawn         Electrical connection rating (W)       0         Gas connection rating (W)       7800         Gas type       G20         Current (A)       0,6         Voltage (V)       220-240         Frequency (Hz)       50/60         Length of Electrical Supply Cord (cm)       85         Plug type       No         Gas connection       N/A         Width of the product       590         Height of the product       49         Depth of the product       510         Minimum niche height       41         Minimum niche width       560         Niche depth       490         Net weight (kg)       12.3	Number of electric plates	0
Number of induction plates       0         Number of electric warming zones       0         Location of control panel       Front         Basic surface material       Glass         Main colour of product       Silver Dawn         Electrical connection rating (W)       0         Gas connection rating (W)       7800         Gas type       G20         Current (A)       0,6         Voltage (V)       220-240         Frequency (Hz)       50/60         Length of Electrical Supply Cord (cm)       85         Plug type       No         Gas connection       N/A         Width of the product       590         Height of the product       49         Depth of the product       510         Minimum niche height       41         Minimum niche width       560         Niche depth       490         Net weight (kg)       12.3	Number of radiant plates	0
Number of electric warming zones  Location of control panel  Basic surface material  Glass  Main colour of product  Electrical connection rating (W)  Gas connection rating (W)  Gas type  G20  Current (A)  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  Gas connection  N/A  Width of the product  Depth of the product  Minimum niche height  Minimum niche width  Niche depth  Net weight (kg)  Front  Front  Front  Front  Front  Front  Front  Front  Front  Bass  No  0  0  0  0  N/8  7800  0  0  0  0  0  0  0  0  0  0  0  0	Number of halogen plates	0
Location of control panel  Basic surface material  Glass  Main colour of product  Electrical connection rating (W)  Gas connection rating (W)  Gas type  G20  Current (A)  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  No  Gas connection  N/A  Width of the product  Depth of the product  Minimum niche height  Minimum niche width  Net weight (kg)  Net Silver Dawn  G20  Current  A 0,6  Con,6  Con,6	Number of induction plates	0
Basic surface materialGlassMain colour of productSilver DawnElectrical connection rating (W)0Gas connection rating (W)7800Gas typeG20Current (A)0,6Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)85Plug typeNoGas connectionN/AWidth of the product590Height of the product49Depth of the product510Minimum niche height41Minimum niche width560Niche depth490Net weight (kg)12.3	Number of electric warming zones	0
Main colour of product  Electrical connection rating (W)  Gas connection rating (W)  Gas type  Gurrent (A)  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  No  Gas connection  N/A  Width of the product  Begin to perform the product  Minimum niche height  Minimum niche width  Net weight (kg)  Silver Dawn  0  Silver Dawn  0  N 7800  820  Current (A)  0,6  220-240  Frequency (Hz)  50/60  85  Plug type  No  6as connection  N/A  Width of the product  590  Height of the product  590  Minimum niche width  560  Niche depth  Net weight (kg)  12.3	Location of control panel	Front
Electrical connection rating (W)         0           Gas connection rating (W)         7800           Gas type         G20           Current (A)         0,6           Voltage (V)         220-240           Frequency (Hz)         50/60           Length of Electrical Supply Cord (cm)         85           Plug type         No           Gas connection         N/A           Width of the product         590           Height of the product         49           Depth of the product         510           Minimum niche height         41           Minimum niche width         560           Niche depth         490           Net weight (kg)         12.3	Basic surface material	Glass
Gas connection rating (W)         7800           Gas type         G20           Current (A)         0,6           Voltage (V)         220-240           Frequency (Hz)         50/60           Length of Electrical Supply Cord (cm)         85           Plug type         No           Gas connection         N/A           Width of the product         590           Height of the product         49           Depth of the product         510           Minimum niche height         41           Minimum niche width         560           Niche depth         490           Net weight (kg)         12.3	Main colour of product	Silver Dawn
Gas type         G20           Current (A)         0,6           Voltage (V)         220-240           Frequency (Hz)         50/60           Length of Electrical Supply Cord (cm)         85           Plug type         No           Gas connection         N/A           Width of the product         590           Height of the product         49           Depth of the product         510           Minimum niche height         41           Minimum niche width         560           Niche depth         490           Net weight (kg)         12.3	Electrical connection rating (W)	0
Current (A)         0,6           Voltage (V)         220-240           Frequency (Hz)         50/60           Length of Electrical Supply Cord (cm)         85           Plug type         No           Gas connection         N/A           Width of the product         590           Height of the product         49           Depth of the product         510           Minimum niche height         41           Minimum niche width         560           Niche depth         490           Net weight (kg)         12.3	Gas connection rating (W)	7800
Voltage (V)         220-240           Frequency (Hz)         50/60           Length of Electrical Supply Cord (cm)         85           Plug type         No           Gas connection         N/A           Width of the product         590           Height of the product         49           Depth of the product         510           Minimum niche height         41           Minimum niche width         560           Niche depth         490           Net weight (kg)         12.3	Gas type	G20
Frequency (Hz) 50/60  Length of Electrical Supply Cord (cm) 85  Plug type No  Gas connection N/A  Width of the product 590  Height of the product 49  Depth of the product 510  Minimum niche height 41  Minimum niche width 560  Niche depth 490  Net weight (kg) 12.3	Current (A)	0,6
Length of Electrical Supply Cord (cm)  Plug type  No Gas connection  N/A  Width of the product  Height of the product  Depth of the product  Minimum niche height  Minimum niche width  Niche depth  Net weight (kg)  85  No	Voltage (V)	220-240
Plug type No Gas connection N/A Width of the product 590 Height of the product 49 Depth of the product 510 Minimum niche height 41 Minimum niche width 560 Niche depth 490 Net weight (kg) 12.3	Frequency (Hz)	50/60
Gas connection N/A Width of the product 590 Height of the product 49 Depth of the product 510 Minimum niche height 41 Minimum niche width 560 Niche depth 490 Net weight (kg) 12.3	Length of Electrical Supply Cord (cm)	85
Width of the product 590  Height of the product 49  Depth of the product 510  Minimum niche height 41  Minimum niche width 560  Niche depth 490  Net weight (kg) 12.3	Plug type	No
Height of the product 49  Depth of the product 510  Minimum niche height 41  Minimum niche width 560  Niche depth 490  Net weight (kg) 12.3	Gas connection	N/A
Depth of the product 510  Minimum niche height 41  Minimum niche width 560  Niche depth 490  Net weight (kg) 12.3	Width of the product	590
Minimum niche height       41         Minimum niche width       560         Niche depth       490         Net weight (kg)       12.3	-	49
Minimum niche width 560 Niche depth 490 Net weight (kg) 12.3	Depth of the product	510
Niche depth 490 Net weight (kg) 12.3	Minimum niche height	41
Net weight (kg) 12.3	Minimum niche width	560
	Niche depth	490
Automatic programmes No	Net weight (kg)	12.3
	Automatic programmes	No

TEHNILISED OMADUSED		
Power on indicator	No	
Number of indicators	0	
Type of regulation	Semirapid	
Type of lid	Without	
Residual heat indicator	Without	
Main on/off switch	No	
Safety device	-	
Timer	No	

ENERGIAMÄRGIS	
Energy input	Gas